

1163.07 PARKING SPACES FOR PEOPLE WITH DISABILITIES.

Parking spaces designated for people with disabilities shall be in compliance with the universal parking space design set forth in the Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities.

The number and location of the designated spaces shall be in compliance with the requirements of such Americans with Disabilities Act Accessibility Guidelines (ADAAG 4.1.2 5A) as follows:

<u>Total Parking in Lot</u>	<u>Required Minimum Number of Accessible Spaces</u>
1 to 25	1
26 to 50	2
51 to 75	3
76 to 100	4
101 to 150	5
151 to 200	6
201 to 300	7
301 to 400	8
401 to 500	9
501 to 1000	2 percent of total
1001 and over	20 plus 1 for each 100 over 1000

Such accessible spaces shall have the minimum dimensions of eleven **EIGHT** feet wide **MINIMUM** and nineteen feet deep, with a five foot wide access aisle on one side. **AT LEAST ONE IN EVERY EIGHT ACCESSIBLE PARKING SPACES, BUT NOT LESS THAN ONE, SHALL BE SERVED BY AN ACCESS AISLE EIGHT FEET WIDE MINIMUM AND SHALL BE DESIGNATED "VAN ACCESSIBLE". AN ACCEPTABLE ALTERNATIVE TO THE PROVISION OF A PERCENTAGE OF SPACES TO BE VAN ACCESSIBLE AND THE ASSOCIATED NEED TO INCLUDE ADDITIONAL SIGNAGE IS TO PROVIDE ALL ACCESSIBLE PARKING SPACES ELEVEN FEET WIDE SERVED BY AN ACCESS AISLE FIVE FEET WIDE.** This access aisle shall also be connected to an accessible route to the appropriate accessible entrance of a building or facility. This access aisle shall either blend with the accessible route or have an adjoining ramp with a minimum width of three feet and a slope not to exceed 1:20.

All such spaces shall be designated by free-standing signs pursuant to the Ohio Manual of Uniform Traffic Control Devices, type R-59 A and/or R-59-B.

Such signs shall be emblazoned with the "international symbol of accessibility", and be located at the interior end and at mid-point of the space, mounted either on a pole **OR WALL** at a minimum height of eighty **SIXTY** inches above grade **TO THE TOP OF THE SIGN** ~~or on a wall a minimum of forty-eight inches above finished grade.~~

~~Any such handicapped parking spaces which are not currently designated as set forth herein shall be brought into compliance with this provision by July 26, 1995.~~

(Ord. 131-93. Passed 6-15-93.)

EXHIBIT A